

Green Glue

Noiseproofing Sealant

A waterbased sealant used to seal edges and seams of the drywall and subfloor to maintain the specific Sound Transmission Class (STC) value of the system designed. SilenSeal can be easily mudded and painted over. It cleans up with simple soap and water. SilenSeal remains permanently flexible and will not crack. SilenSeal adheres to most surfaces including wood, concrete, metal, glass, plastic and gypsum.

Finally a replacement for that messy black sealant !

- ✓ ***Water based***
- ✓ ***Easy to apply***
- ✓ ***Low odor***
- ✓ ***Non-toxic***
- ✓ ***No VOC formulation***
- ✓ ***Water clean-up***
- ✓ ***Freeze / thaw stable***
- ✓ ***Paintable, muddable***

CONTACT

Tel. 905-625-8944 Fax 905-625-7142
 Toll Free 1-888-625-8944
 Email info@acoustiguard.com
 Website www.acoustiguard.com



SPECIFICATIONS

Appearance.....Brown Creamy Paste
 Solids..... 67-70% by weight
 Viscosity..... 980,000 cps +/- 10% # spindle 1rpm
 PH 7 -7.5
 Flammability Non-Flammable
 VOC Content5 gr/liter (calculated)
 Cure Time 2-7 days
 Application temperature 40°F min
 Storage 40 to 100 deg F
 Clean Up Soap and Water
 Shelf Life 1 year

COVERAGE

29 oz. Tube

3/8" bead	40 linear ft.
1/4" bead	89 linear ft.